02 41 19 Demo FRP & Base at walls; typical at all bathroom 003 interiors unless otherwise noted 02 41 19 Remove floor tile and substrate

004 02 41 19 Remove Ceiling Tile Only in the Room; repair grid 006

Coordinate measurements with new construction 007

08 11 13 Install new 36" HM Door and Frame with new 002 Replace all door hardware with new at existing leaf

09 05 05 01 Install leveling compound as needed for smooth

appearance of new tile & a flush threshold to adjacent floors, typical on new floor tile 09 30 13 Install new floor tile; slope to floor drain is drain

09 30 13 Install new wall tile flush and straight with accent top piece, floor to highest partial wall or window sill height; typical at bathroom interior unless noted

09 30 13 Install new wall tile flush and straight, floor to ceiling at this plumbing wall only

09 30 13 Install accent tile at this wall

006 09 51 23 Install new ceiling tile into existing grid here

10 21 13.19 Install new toilet partitions (typical)

10 28 13 Install wall hung mirror here; center over fixture unless noted otherwise


Install hand dryer here; coordinate with electrical & 002 mechanical Coordinate new fixture installations with 22 42 00

mechanical, typical for new 001


22 47 13 Install double drinking fountain here; coordinate with mechanical & electrical drawings



Front of School



Mens 67




Womens 66



Mens 94

Womens 92




Typical Toilet Room Wall

3/4" = 1'-0"

See Mech. 1'-6"

3'-0"

Hand Dryer



See Spec for Sizing



DALE

AN ASSOCIATION

Architects

One Jackson Place 250

188 East Capitol Street Jackson, MS 39201

p 601.352.5411

201 Park Court Suite B Ridgeland, MS 39157

p 601.790.9432

161 Lameuse St. Suite 201

Biloxi, MS 39530 p 228.374.1409

dalebaileyplans.com

Not For

Construction


District

onsolidate

Sunflower

Ruleville Middle

	-
Project No	005
Date	June 2021
Revisions	Rev Date
1	10/5/2021
2	11/26/2021



1 RCP - Demolition
3/32" = 1'-0"

General Demolition Notes

1. Where floor transitions from new floor to existing floor, a floor transition strip is to be provided. A knock-down frame is to be provided in place of the existing frame where the opening is a part of corridor.

2. Remove all existing flooring, ceiling tile, rubber base, etc.. where shown to be replaced by new materials in the finish

schedule. RE: Floors plans, RCP, and Finish Schedule 3. Owner has right of refusal for all demo work. If not retained,

GC to be responsible for disposal. 4. Verify all existing conditions. Notify architect of any discrepancies between the existing conditions and these documents. The Contractor is to consider the additional work required by any discrepancies to be included in this 5. Burying or Burning of materials will not be permitted on

6. Repair any damage caused to building construction

identified to remain.

7. Refer to other discipline drawings for additional demolition information as noted

8. Schedule with the Owner any demolition that involves exposing to the weather the interior portions of building to remain. This work is to be performed during good, dry weather or temporary waterproof barrier walls shall be constructed at all occurrences where the demolition exposes weather to the interior of portions of buildings to

9. Existing loose school property to be the responsibility of the school district, removal of property by owner to be coordinated between the contractor and school district.

10. Where areas are removed or altered, patch, repair, & paint to match adjacent surface material and finish. 11. Remove partitions and existing fixtures.

Specific Notes

Ceiling Legend

Moisture Resistant Acoustical Lay In Ceiling Colored Acoustical Lay In Ceiling

Vinyl Faced Acoustical Lay In Ceiling

Gypsum Board Ceiling

2x2 Acoustical Lay In Ceiling Plaster/Stucco

Concealed Fastender Painted Metal Soffit

Surface-Mounted Fluorescent Light Fixture

2x2 Fluorescent Fixture

Recessed Can Light Fixture

HVAC Supply Grille

HVAC Return Grille


Exterior Wall Light

Interior Wall Light

Open to Structure (OTS)

A-041

Composite RCP



Architects

One Jackson Place 250 188 East Capitol Street Jackson, MS 39201 p 601.352.5411

201 Park Court Suite B Ridgeland, MS 39157 p 601.790.9432

161 Lameuse St. Suite 201 Biloxi, MS 39530 p 228.374.1409

dalebaileyplans.com



District

onsolidated

Sunflower

Design

Development

June 2021 Rev Date

10/5/2021 11/26/2021

Architects

One Jackson Place 250 188 East Capitol Street Jackson, MS 39201 p 601.352.5411

201 Park Court Suite B Ridgeland, MS 39157 p 601.790.9432

161 Lameuse St. Suite 201 Biloxi, MS 39530 p 228.374.1409


dalebaileyplans.com

Specific Notes

22 47 13 001 Install double drinking fountain here; coordinate with mechanical & electrical drawings

Not For Construction

District 3 38771



Library 77 Teachers Lounge 144

Office 83 145

Office 84

Room

Lounge 86

Classroom

96

Classroom 90

Classroom 95

A-402

2 A-402

Storage 97

22 47 13 001

Classroom 91

Ruleville Middle Main Building - New Construction

3/32" = 1'-0"

Princ. A/C 143 98 70

Recept 71

Vault

75

Storage 74

Storage 73

Design Development

Ruleville Middle

Sunflower

 Project No
 005

 Date
 June 2021

 Revisions
 Rev Date

 1
 10/5/2021


 2
 11/26/2021

A-101

Composite Floor Plan

1 RCP - New Construction

3/32" = 1'-0"



Ceiling Edge Trim Detail

General RCP Notes

- All ceiling heights shall be same as existing or lower, unless
- noted otherwise.

 2. Contractor shall paint all surfaces above 10'-0" at wall, roof, and ceiling, as well as anything attached therein at all exposed sections of ceilings where not covered by new 2x2 ACT unless noted otherwise.
 - ACT, unless noted otherwise

 3. Repair/replace any and all ceiling damaged due to construction activities.
- 4. Bent ceiling grid damaged due to construction activities shall be replaced or bent to appear as new in shape.
- 5. ACT in auditorium to be reveal edged

DALE BAILEY AN ASSOCIATION

Architects

One Jackson Place 250 188 East Capitol Street Jackson, MS 39201 p 601.352.5411

201 Park Court Suite B Ridgeland, MS 39157 p 601.790.9432

161 Lameuse St. Suite 201 Biloxi, MS 39530 p 228.374.1409

Specific Notes



Distric

Olid

unflower

dalebaileyplans.com

Ceiling Legend Moisture Resistant Acoustical Lay In Ceiling Colored Acoustical Lay In Ceiling Vinyl Faced Acoustical Lay In Ceiling Gypsum Board Ceiling 2x2 Acoustical Lay In Ceiling Plaster/Stucco Concealed Fastender Painted Metal Soffit 2x2 Fluorescent Fixture Surface-Mounted Fluorescent Light Fixture Recessed Can Light Fixture HVAC Supply Grille HVAC Return Grille Exterior Wall Light Open to Structure (OTS)

Design Development

Project No	005
Date	June 2021
Revisions	Rev Date
1	10/5/2021
2	11/26/2021

A-141

Composite RCP

& mechanical

22 42 00 001 Coordinate new fixture installations with

mechanical, typical for new

- floor transition strip is to be provided. A knock-down frame is to be provided in place of the existing frame where the opening is a part of corridor. 2. Remove all existing flooring, ceiling tile, rubber base, etc..
- where shown to be replaced by new materials in the finish schedule. RE: Floors plans, RCP, and Finish Schedule
- 3. Owner has right of refusal for all demo work. If not retained, GC to be responsible for disposal.
- discrepancies between the existing conditions and these documents. The Contractor is to consider the additional work required by any discrepancies to be included in this Contract. 5. Burying or Burning of materials will not be permitted on
- identified to remain.
- exposing to the weather the interior portions of building to remain. This work is to be performed during good, dry weather or temporary waterproof barrier walls shall be constructed at all occurrences where the demolition exposes weather to the interior of portions of buildings to
- 9. Existing loose school property to be the responsibility of the school district, removal of property by owner to be coordinated between the contractor and school district.
- 10. Where areas are removed or altered, patch, repair, & paint
- 11. Remove partitions and existing fixtures.

Design Development

Olid

nflower

Development		
Project No	005	
Date	June 2021	
Revisions	Rev Date	
1	10/5/2021	
2	11/26/2021	

General Finish Plan Notes

- 1. All flooring transitions are to occur at center line of door
- 2. New Fixture locations shall be coordinated with mechanical sheets.
- 3. Install new tile base at all walls in bathrooms
- 4. Install new grab bars at all ADA toilets 5. Install 5/8" drywall at upper wall (3'-6" AFF To 2" Above Ceiling) with adhesive and mechanical fasteners; finish and paint with epoxy
- 6. Install moisture resistant back board at all new tile.

AN ASSOCIATION

Architects

One Jackson Place 250 188 East Capitol Street Jackson, MS 39201 p 601.352.5411

201 Park Court Suite B Ridgeland, MS 39157 p 601.790.9432

161 Lameuse St. Suite 201 Biloxi, MS 39530 p 228.374.1409

dalebaileyplans.com

Not For

Construction

Specific Notes

02 41 19 002	Dashed lines indicated extent of demoed work
02 41 19 003	Demo FRP & Base at walls; typical at all bathroom interiors unless otherwise noted
02 41 19 004	Remove floor tile and substrate
02 41 19 007	Coordinate measurements with new construction
08 11 13 002	Install new 36" HM Door and Frame with new hardware
08 71 00 001	Replace all door hardware with new at existing leaf
09 05 05 01	Install leveling compound as needed for smooth appearance of new tile & a flush threshold to adjacent floors, typical on new floor tile
09 30 13 001	Install new floor tile; slope to floor drain is drain provided
09 30 13 003	Install new wall tile flush and straight with accent top piece, floor to highest partial wall or window sill height; typical at bathroom interior unless noted otherwise
09 30 13 005	Install new wall tile flush and straight, floor to ceiling at this plumbing wall only
09 30 13 006	Install accent tile at this wall
10 21 13.19 001	Install new toilet partitions (typical)
10 28 13 001	Install wall hung mirror here; center over fixture unless noted otherwise

- 1. Where floor transitions from new floor to existing floor, a
- 4. Verify all existing conditions. Notify architect of any
- 6. Repair any damage caused to building construction
- 7. Refer to other discipline drawings for additional demolition information as noted 8. Schedule with the Owner any demolition that involves

- to match adjacent surface material and finish.

2 Central Toilets - New Construction

02 41 19 007----

Women 66

//---------

F=========

_08 11 13 002-

10 28 13 002—

Women 66

22 42 00 001

10 28 13 001[/]

=====

67

02 41 19 004

--02 41 19 003

Men 67

_10 21 13.19

22 42 00 001

__09 30 13 003

___09 05 05 01 /

─09 30 13 005

---09 30 13 006

5' - 0"

--09 30 13 001

—10 28 13 002

—10 28 13 001

--02 41 19 002

--02 41 19 003

/c============

Central Toilets - Existing

1 1/2" = 1'-0"

02 41 19 004—

09 30 13 003—

Storage

10 21 13.19_

5' - 0"

153

08 71 00 001-

09 30 13 006-

09 30 13 005

A-401

Central Toilets

1 West Toilets - Existing

West Toilets - New Construction

1/2" = 1'-0"

General Finish Plan Notes

1. All flooring transitions are to occur at center line of door

2. New Fixture locations shall be coordinated with mechanical

3. Install new tile base at all walls in bathrooms

4. Install new grab bars at all ADA toilets 5. Install 5/8" drywall at upper wall (3'-6" AFF To 2" Above Ceiling) with adhesive and mechanical fasteners; finish and

paint with epoxy 6. Install moisture resistant back board at all new tile.

DALE AN ASSOCIATION

Architects

One Jackson Place 250 188 East Capitol Street Jackson, MS 39201 p 601.352.5411

201 Park Court Suite B Ridgeland, MS 39157 p 601.790.9432

161 Lameuse St. Suite 201 Biloxi, MS 39530 p 228.374.1409

dalebaileyplans.com

Not For

Distric

Specific Notes

Construction 02 41 19 002 Dashed lines indicated extent of demoed work 02 41 19 003 Demo FRP & Base at walls; typical at all bathroom

interiors unless otherwise noted 02 41 19 004 Remove floor tile and substrate 08 11 13 002 Install new 36" HM Door and Frame with new

_09 05 05 01 __Install leveling compound as needed for smooth appearance of new tile & a flush threshold to adjacent floors, typical on new floor tile 09 30 13 003 Install new wall tile flush and straight with accent

height; typical at bathroom interior unless noted otherwise 09 30 13 005 Install new wall tile flush and straight, floor to

top piece, floor to highest partial wall or window sill

ceiling at this plumbing wall only 09 30 13 006 Install accent tile at this wall

10 21 13.19 Install new toilet partitions (typical)

10 28 13 001 Install wall hung mirror here; center over fixture -unless-noted otherwise 10 28 13 002 Install hand dryer here; coordinate with electrical &

mechanical

22 42 00 001 Coordinate new fixture installations with mechanical, typical for new

Design

Devel	ортпени
Project No	005
Date	June 2021
Revisions	Rev Date
1	10/5/2021
2	11/26/2021